

# LIOS BIOIL Colorato

## Colored natural oil treatment for wooden floors



### Description

LIOS BIOIL Colorato is a colored natural oil treatment for wooden floors with easy application, very durable and soft effect on the surface. LIOS BIOIL Colorato is available in 20 different colors, miscible together to make a wide range of new colors.

### Characteristics

Application	buffing machine, rubber trowel, floor polisher, sponge, cloths
Application temperature	+10°C ÷ +25°C
Thinning (if necessary)	LIOS SOLV
Surface dry time	24/48 h <sup>(1)</sup>
Total drying time	15-30 days <sup>(1)</sup>
Coverage	40-60 m <sup>2</sup> /L (depending of the sanding)
Storage stability	1 year <sup>(2)</sup>
Packaging	1 L
Tool cleaning	DILUENTE DNE
1	at 20°C and 65% R.H.
2	in original sealed containers at temperatures between +10°C and +25°C

### Available Versions

#### Range of colors :

* Castagno	* Larice	* Tortora
* Autunno	* Oliva	* Ciliegio
* Vecchio Rovere	* Noce Old	* Grigio
* Fumè	* Noce Classic	* Bianco
* Super Bianco	* Nero	* Wengè
* Teak	* Titanium Grey	* Stone
* Vanilla	* Havana	* on request

### How to use

Shake the product using a stick to have a homogeneous mixture. LIOS BIOIL Colorato has to be applied to wooden floors that have been filled and sanded with 120 paper grit, than use High Pro felt disc to make the surface absorbs the product evenly. Alternatively, finish the floor with 150 paper grit. Apply LIOS BIOIL Colorato on the floor, working the product in order to help its penetration into the wood grain.

After 15-20 minutes buff the surface using a buffing machine with a white pad and a cloth to remove the excess of oil and have a uniform and smooth effect.

For small dimension rooms use a cloth instead a buffing machine. After 24 hours, apply LIOS BALM FISSATIVO, OIL WOOD TRAFFIK, LIOS NATURAL WAX, LIOS HARD WAX BIOIL, LIOS HARD WAX BIOIL 3D, OIL WAX PLUS or LIOS HARD WAX BIOIL 90 (see technical data sheets).

After 72 hours it is possible to apply ECOSTAR 2K or DUROLACK MC 50 (see technical data sheets).

### Notes

In order to prevent future yellowing of the product, we strongly recommend to follow this cycle LIOS Bioil Bianco / LIOS Bioil Super Bianco and after 3 days CHIM TABU FD and ECOSTAR 2K (see technical data sheets).

If the surface to be treated is wide, we suggest to pour all the cans of product into a big one and than proceed with the application.

An un-even sanding of the wooden floor causes not homogeneous absorption of the product.

### Warnings

*Cloths, rollers, pads used for the application (even sanding dust), must be soaked in water immediately after use in order to avoid the risk of self-ignition.*

### Label elements

· Flammable liquid and vapour.· May be fatal if swallowed and enters airways.

· Repeated exposure may cause skin dryness or cracking.· Contains . May produce an allergic reaction.

· If medical advice is needed, have product container or label at hand.· Keep out of reach of children.· Keep away from heat / sparks / open flames / hot surfaces. No smoking.· Keep container tightly closed.· Wear protective gloves / protective clothing / eye protection / face protection.· IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician.· Dispose your waste in dedicated collection points.

Contents:2-BUTANONO OXIME ; Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics; HEAVY HYDRODESULPHURATED NAPHTHA (TURPENTINE SUBSTITUTE); ETHYLBENZENE ;



### Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



[http://www.chimiver.com/tds/EN\\_LIOS\\_BIOIL\\_Colorato.pdf](http://www.chimiver.com/tds/EN_LIOS_BIOIL_Colorato.pdf)